



ELECTRONIC AND CONTROL PROCESS DEVICES

"SMART SERIES" Temperature and signal transmitters and converters for DIN rail mounting

The SMART series devices can accept on their input several types of signals coming from the field; the series is composed of:

- 4÷20 mA two wires isolated Transmitter for universal input (**DAT4035**)
- Isolated Converters for universal input with configurable output as voltage or current (**DAT4135, DAT 4235**)
- Isolated Converter for universal input with configurable output as voltage or current and trip amplifier (**DAT4520**)

INDEX

- 12 • **DAT 4035**
PC programmable Two wire isolated universal signal transmitter
- 13 • **DAT 4135**
PC programmable isolated universal signal converter
- 14 • **DAT 4135/SEL**
PC configurable universal signal converter with command of enable/disable output
- 15 • **DAT 4235**
PC programmable 3 ways isolated universal signal converter
- 16 • **DAT 4520**
Universal converter with Trip Amplifier

SMART SERIES

02

DATEXEL



SMART series Temperature and signal
transmitters and converters for
DIN rail mounting

DAT 4035**GENERAL DESCRIPTION**

The transmitter DAT 4035 is able to execute many functions such as: measure and linearisation of the temperature characteristic of RTDs sensors, conversion of a linear resistance variation, conversion of a standard active current signal, conversion of a voltage signal even coming from a potentiometer connected on its input. Moreover the DAT 4035 is able to measure and linearise the standard thermocouples with internal cold junction compensation. The measured values are converted in a 4÷20 mA current signal. The device guarantees high accuracy and performances stability both in time and in temperature.

FEATURES

- Configurable input for RTD, TC, mV, V, mA, Resistance and Potentiometer
- High accuracy
- Configurable by Personal Computer
- 4 ÷ 20 mA configurable output on current loop

- On-field reconfigurable
- Galvanic isolation at 2000 Vac
- Programming of the unit measure as °C or °F
- EMC compliant – CE mark
- Suitable for DIN rail mounting in compliance with EN-50022 and EN-50035

**Application areas**

POWER SUPPLY		ISOLATION VOLTAGE		TEMPERATURE & HUMIDITY	
Power supply voltage	10 .. 30 Vdc	Input/Power supply	2000 Vac 50 Hz, 1 min.	Operative temperature	-20°C .. +70°C
Reverse polarity protection	60 Vdc max.			Storage temperature	-40°C .. +85°C
				Humidity (not condensed)	0 .. 90 %

EMC (for industrial environments)		HOUSING	
Directive 2004/108/EC		Material	Self-extinguishing plastic
Immunity	EN 61000-6-2	Dimensions (mm)	W x L x H : 90 x 112 x 12.5
Emission	EN 61000-6-4	Weight	about 90 g.

INPUT						
Input type	Min	Max	Span min			
TC (CJC int./ext.)						
J	-200°C	1200°C	2 mV			
K	-200°C	1370°C	2 mV			
S	-50°C	1760°C	2 mV			
R	-50°C	1760°C	2 mV			
B	400°C	1820°C	2 mV			
E	-200°C	1000°C	2 mV			
T	-200°C	400°C	2 mV			
N	-200°C	1300°C	2 mV			
RTD 2,3,4 wires						
Pt100	-200°C	850°C	50°C			
Pt1000	-200°C	200°C	50°C			
Ni100	-60°C	180°C	50°C			
Ni1000	-60°C	150°C	50°C			
Voltage						
mV	-400 mV	+400 mV	2 mV			
mV	-100 mV	+700 mV	2 mV			
Volt	- 10 V	+10 V	500 mV			
Potentiometer (Nominal value)	0 Ω	200 Ω	10 %			
	200 Ω	500 Ω	10 %			
	0.5 KΩ	50 KΩ	10 %			
Resistance 2,3,4 wires						
Low	0 Ω	300 Ω	10 Ω			
High	0 Ω	2000 Ω	200 Ω			
Current mA	-10 mA	+24 mA	2 mA			
Input impedance						
TC, mV	>= 10 MΩ					
Volt	>= 1 MΩ					
Current	~ 50 Ω					
INPUT						
Input calibration (1)						
RTD	the higher of ±0.1% f.s. and ±0.2°C					
Res. Low	the higher of ±0.1% f.s. and ±0.15 Ω					
Res. High	the higher of ±0.2% f.s. and ±1 Ω					
mV, TC	the higher of ±0.1% f.s. and ±18 uV					
Volt	the higher of ±0.1% f.s. and ± 2 mV					
mA	the higher of ±0.1% f.s. and ± 6 uA					
Linearity (1)						
TC	± 0.2 % f.s.					
RTD	± 0.1 % f.s.					
Line resistance influence (1)						
TC, mV/V	<=0.4 uV/Ohm					
RTD 3 wires	0.05 %/Ω (50 Ω balanced max.)					
RTD 4 wires	0.005 %/Ω (100 Ω balanced max.)					
RTD excitation current						
Typical	0.350 mA					
CJC Comp.	± 0.5 °C					
Thermal drift (1)						
Full scale	± 0.01 % / °C					
CJC	± 0.01 % / °C					
Burn-out values						
Max. value output	about 22.5 mA					
Min. value output	about 3.6 mA					
Response time (10÷90% of f.s.)	about 400 ms					
(1) referred to input Span (difference between max. and min. values)						
OUTPUT						
Output type	Min	Max	Span min			
Direct current	4 mA	20 mA	4 mA			
Reverse current	20 mA	4 mA	4 mA			
Output calibration						
Current	± 7 uA					

PC PROGRAMMABLE ISOLATED UNIVERSAL SIGNAL CONVERTER

DAT 4135



GENERAL DESCRIPTION

The converter DAT 4135 is able to execute many functions such as: measure and linearisation of the temperature characteristic of RTDs sensors, conversion of a linear resistance variation, conversion of a standard active current signal, conversion of a voltage signal even coming from a potentiometer connected on its input. Moreover the DAT 4135 is able to measure and linearise the standard thermocouples with internal cold junction compensation.

In function of programming, the measured values are converted in a current or voltage signal. The device guarantees high accuracy and performances stability both in time and in temperature.

FEATURES

- Configurable input for RTD, TC, mV, V, mA, Resistance and Potentiometer
- High accuracy
- Configurable by Personal Computer
- Configurable output in current or voltage

- On-field reconfigurable
- Galvanic isolation at 2000 Vac
- Programming of the unit measure as °C or °F
- EMC compliant – CE mark
- Suitable for DIN rail mounting in compliance with EN-50022 and EN-50034



Application areas



POWER SUPPLY		ISOLATION VOLTAGE		TEMPERATURE & HUMIDITY	
Power supply voltage		Input/Power supply-Output 2000 Vac 50 Hz, 1 min.		Operative temperature	
OUTPUT LOAD RESISTANCE (RLOAD)			-20°C .. +70°C		
Current output		</= 650 Ω		Storage temperature	
Voltage output		>/= 3.5 KΩ		-40°C .. +85°C	
Limitation current		about 25 mA		Humidity (not condensed)	
0 .. 90 %					
CURRENT CONSUMPTION		EMC (for industrial environments)			HOUSING
Current output		DIRECTIVE 2004/108/EC			Material
40 mA max.		Immunity		EN 61000-6-2	
Voltage output		Emission		EN 61000-6-4	
				Dimensions (mm)	
				W x L x H : 90 x 112 x 12.5	
				Weight	
				about 90 g.	

INPUT			
Input impedance			
TC, mV			>= 10 MΩ
Volt			>= 1 MΩ
Current			~ 50 Ω
Linearity (1)			
TC			± 0.2 % f.s.
RTD			± 0.1 % f.s.
Line resistance influence (1)			
TC, mV,V			<=0.8 uV/Ohm
RTD 3 wires			0.05 %/Ω (50 Ω balanced max.)
RTD 4 wires			0.005 %/Ω (100 Ω balanced max.)
RTD excitation current			
Typical			0.350 mA
CJC Comp.			
Thermal drift (1)			
Full scale			± 0.01 % / °C
CJC			± 0.01 % / °C
Burn-out values			
Max. value output			about 23 mA or 10.8 Vdc
Min. value output			about 0 mA or 0 Vdc
Response time (10÷90% of f.s.)			
(1) referred to input Span (difference between max. and min. values)			
OUTPUT			
Output type		Min	Max
Direct current		0 mA	20 mA
Reverse current		20 mA	0 mA
Direct voltage		0 V	10 V
Reverse voltage		10 V	0 V
Output calibration			
Current		± 7 uA	
Voltage		± 5 mV	

DAT 4135/SEL



GENERAL DESCRIPTION

The converter DAT 4135/SEL is able to execute many functions such as: measure and linearisation of the temperature characteristic of RTDs sensors, conversion of a linear resistance variation, conversion of a standard active current signal, conversion of a voltage signal even coming from a potentiometer connected on its input. Moreover the DAT 4135/SEL is able to measure and linearise the standard thermocouples with internal cold junction compensation. In function of programming, the measured values are converted in a current or voltage signal. The device guarantees high accuracy and performances stability both in time and in temperature.

FEATURES

- Configurable input for RTD, TC, mV, V, mA, Resistance and Potentiometer
- High accuracy
- Configurable by Personal Computer
- Configurable output in current or voltage
- On-field reconfigurable

- Galvanic isolation at 2000 Vac
- Programming of the unit measure as °C or °F
- EMC compliant – CE mark
- Suitable for DIN rail mounting in compliance with EN-50022 and EN-50035



Application areas



POWER SUPPLY		ISOLATION VOLTAGE		SEL INPUT COMMAND	
Power supply voltage	18 .. 30 Vdc	Input/Power supply-Output	2000 Vac 50 Hz, 1 min.	Disable output	4÷30 Vdc
OUTPUT LOAD RESISTANCE (RLOAD)		TEMPERATURE & HUMIDITY		HOUSING	
Reverse polarity protection	60 Vdc max.	Current output	</= 650 Ω	Operative temperature	-20°C .. +70°C
		Voltage output	>/= 3.5 KΩ	Storage temperature	-40°C .. +85°C
		Limitation current	20 mA max.	Humidity (not condensed)	0 .. 90 %
CURRENT CONSUMPTION		EMC (for industrial environments)		Material	
Current output	40 mA max.	DIRECTIVE 2004/108/EC		Dimensions (mm)	W x L x H : 90 x 112 x 12.5
Voltage output	20 mA max.	Immunity	EN 61000-6-2	Weight	about 90 g.
		Emission	EN 61000-6-4		

INPUT				INPUT			
Input type				Input impedance			
TC (CJC int./ext.)				TC, mV	>= 10 MΩ		
J	-200°C	1200°C	2 mV	Volt	>= 1 MΩ		
K	-200°C	1370°C	2 mV	Current	~ 50 Ω		
S	-50°C	1760°C	2 mV	Linearity (1)			
R	-50°C	1760°C	2 mV	TC	± 0.2 % f.s.		
B	400°C	1820°C	2 mV	RTD	± 0.1 % f.s.		
E	-200°C	1000°C	2 mV	Line resistance influence (1)			
T	-200°C	400°C	2 mV	TC, mV/V	<=0.8 uV/Ohm		
N	-200°C	1300°C	2 mV	RTD 3 wires	0.05%/Ω (50 Ω balanced max.)		
RTD 2,3,4 wires				RTD 4 wires	0.005%/Ω (100 Ω balanced max.)		
Pt100	-200°C	850°C	50°C	RTD excitation current			
Pt1000	-200°C	200°C	50°C	Typical	0.350 mA		
Ni100	-60°C	180°C	50°C	CJC Comp.			
Ni1000	-60°C	150°C	50°C	Thermal drift (1)			
Voltage				Full scale	± 0.01% / °C		
mV	-400 mV	+400 mV	2 mV	CJC	± 0.01% / °C		
mV	-100 mV	+700 mV	2 mV	Burn-out values			
Volt	- 10 V	+10 V	500 mV	Max. value output	about 23 mA or 10.8 Vdc		
	0 Ω	200 Ω	10%	Min. value output	about 0 mA or 0 Vdc		
Potentiometer (Nominal value)				Response time (10÷90% of f.s.)			
	200 Ω	500 Ω	10%	about 400 ms			
	0.5 KΩ	50 KΩ	10%				
Resistance 2,3,4 wires							
Low	0 Ω	300 Ω	10 Ω				
High	0 Ω	2000 Ω	200 Ω				
Current mA							
	-10 mA	+24 mA	2 mA				
Input calibration (1)							
RTD	the higher of ±0.1% f.s. and ±0.2°C						
Res. Low	the higher of ±0.1% f.s. and ±0.15 °C						
Res. High	the higher of ±0.2% f.s. and ±1 °C						
mV, TC	the higher of ±0.1% f.s. and ±18 uV						
Volt	the higher of ±0.1% f.s. and ± 2 mV						
mA	the higher of ±0.1% f.s. and ± 6 uA						

OUTPUT			
Output type	Min	Max	Span min
Direct current	0 mA	20 mA	4 mA
Reverse current	20 mA	0 mA	4 mA
Direct voltage	0 V	10 V	1 V
Reverse voltage	10 V	0 V	1 V
Output calibration			
Current	± 7 uA		
Voltage	± 5 mV		

(1) referred to input Span (difference between max. and min. values)

PC PROGRAMMABLE 3 WAYS ISOLATED UNIVERSAL SIGNAL CONVERTER

DAT 4235



GENERAL DESCRIPTION

The converter DAT 4235 is able to execute many functions such as: measure and linearisation of the temperature characteristic of RTDs sensors, conversion of a linear resistance variation, conversion of a standard active current signal, conversion of a voltage signal even coming from a potentiometer connected on its input. Moreover the DAT 4235 is able to measure and linearise the standard thermocouples with internal cold junction compensation. In function of programming, the measured values are converted in a current or voltage signal. The device guarantees high accuracy and performances stability both in time and in temperature.

FEATURES

- Configurable input for RTD, TC, mV, V, mA, Resistance and Potentiometer
- High accuracy
- Configurable by Personal Computer
- Configurable output in current or voltage
- On-field reconfigurable

- Galvanic isolation at 2000 Vac on the 3 ways
- Programming of the unit measure as °C or °F
- EMC compliant – CE mark
- Suitable for DIN rail mounting in compliance with EN-50022 and EN-50035



Application areas



POWER SUPPLY		ISOLATION VOLTAGE		TEMPERATURE & HUMIDITY	
Power supply voltage		Input/Power supply-Output 2000 Vac 50 Hz, 1 min.		Operative temperature -20°C .. +70°C	
OUTPUT LOAD RESISTANCE (RLOAD)		Current output </= 650 Ω		Storage temperature -40°C .. +85°C	
Reverse polarity protection		Voltage output >/= 600 Ω		Humidity (not condensed) 0 .. 90 %	
Limitation current 30 mA max.					
CURRENT CONSUMPTION		EMC (for industrial environments)		HOUSING	
Current output 70 mA max.		DIRECTIVE 2004/108/EC		Material Self-extinguishing plastic	
Voltage output 50 mA max.		Immunity EN 61000-6-2		Dimensions (mm) W x L x H : 90 x 112 x 12.5	
		Emission EN 61000-6-4		Weight about 90 g.	

INPUT			
Input type	Min	Max	Span min
TC (CJC int./ext.)			
J	-200°C	1200°C	2 mV
K	-200°C	1370°C	2 mV
S	-50°C	1760°C	2 mV
R	-50°C	1760°C	2 mV
B	400°C	1820°C	2 mV
E	-200°C	1000°C	2 mV
T	-200°C	400°C	2 mV
N	-200°C	1300°C	2 mV
RTD 2,3,4 wires			
Pt100	-200°C	850°C	50°C
Pt1000	-200°C	200°C	50°C
Ni100	-60°C	180°C	50°C
Ni1000	-60°C	150°C	50°C
Voltage			
mV	-400 mV	+400 mV	2 mV
mV	-100 mV	+700 mV	2 mV
Volt	- 10 V	+10 V	500 mV
Potentiometer (Nominal value)	0 Ω	200 Ω	10%
	200 Ω	500 Ω	10%
	0.5 KΩ	50 KΩ	10%
Resistance 2,3,4 wires			
Low	0 Ω	300 Ω	10 Ω
High	0 Ω	2000 Ω	200 Ω
Current mA	-10 mA	+24 mA	2 mA
Input calibration (1)			
RTD	the higher of ±0.1 % f.s. and ±0.2°C		
Res. Low	the higher of ±0.1 % f.s. and ±0.15 Ω		
Res. High	the higher of ±0.2 % f.s. and ±1 Ω		
mV, TC	the higher of ±0.1 % f.s. and ±18 uV		
Volt	the higher of ±0.1 % f.s. and ± 2 mV		
mA	the higher of ±0.1 % f.s. and ± 6 uA		

INPUT						
Input impedance						
TC, mV	>= 10 MΩ					
Volt	>= 1 MΩ					
Current	~ 50 Ω					
Linearity (1)						
TC	± 0.2 % f.s.					
RTD	± 0.1 % f.s.					
Line resistance influence (1)						
TC, mV,V	<=0.8 uV/Ohm					
RTD 3 wires	0.05 %/Ω (50 Ω balanced max.)					
RTD 4 wires	0.005 %/Ω (100 Ω balanced max.)					
RTD excitation current						
Typical	0.350 mA					
CJC Comp.						
Thermal drift (1)						
Full scale	± 0.01 % / °C					
CJC	± 0.01 % / °C					
Burn-out values						
Max. value output	about 25 mA or 10.8 Vdc					
Min. value output	about -25 mA or -10.8 Vdc					
Response time (10÷90% of f.s.)						
(1) referred to input Span (difference between max. and min. values)						

OUTPUT			
Output type	Min	Max	Span min
Direct current	-20 mA	20 mA	4 mA
Reverse current	20 mA	-20 mA	4 mA
Direct voltage	-10 V	10 V	1 V
Reverse voltage	10 V	-10 V	1 V
Output calibration			
Current	± 7 uA or ± 15 uA (2)		
Voltage	± 10 mV		

(2) referred to the output ± 20 mA.

DAT 4520**GENERAL DESCRIPTION**

The DAT 4520 device measures mV, V, mA or resistance signals, and can be directly connected to Thermocouple, RTD or potentiometer sensors. The input signal is filtered, linearised, amplified and transferred to the output circuit, that converts it in a 0-10V range or 0-20mA range signal. Auxiliary power supply allows to supply the output current loop. Moreover, the device is able to control two trip alarm relay outputs. DAT 4520 has a 3 way isolation: input is 2000 Vac isolated from power supply and output; power supply and output are 1500 Vac isolated between them.

FEATURES

- Configurable input for Tc, RTD, Res, mV, V, mA, Potentiometer
- High accuracy
- Configurable by Personal Computer
- 0 to 10V, 0 to 20mA configurable output
- On-field reconfigurable

- 2000 Vac galvanic isolation between input, output
- Programming of the unit measure as °C or °F
- EMC compliance – CE mark
- Suitable for DIN rail mounting in compliance with EN-50022 and EN-50035

**Application areas**

TRIP ALARMS		Isolation voltage		TEMPERATURE & HUMIDITY	
Output type	n° 2 Relay SPDT	Input/Output	2000 Vac, 50 Hz, 1min.	Operative temperature	-20°C .. +60°C
Contact rating	2A, 250 Vac	Input/Supply	2000 Vac, 50 Hz, 1min.	Storage temperature	-40°C .. +85°C
Load	2A, 30 Vdc	Supply/Output	1500 Vac, 50 Hz, 1min.	Humidity (not condensed)	0 .. 90 %
Minimum load	resistive				
Voltage max	5Vdc, 10mA				
	250 Vac (50/60 Hz)				
	110 Vdc				
Isolation voltage	coil-to-contacts: 2000Vac between contacts: 1000Vac				
POWER SUPPLY		EMC (for industrial environments)		HOUSING	
Power supply voltage	20 .. 30 Vdc	DIRECTIVE 2004/108/EC		Material	Self-extinguishing plastic
Reverse polarity protection	60 Vdc max.	Immunity	EN 61000-6-2	Mounting	DIN Rail
		Emission	EN 61000-6-4	Dimensions (mm)	W x L x H : 120 x 100 x 22.5
				Weight	about 150 g.

INPUT			
Input type	Min	Max	Span min
TC (CJC int./ext.)			
J	-200°C	1200°C	2 mV
K	-200°C	1370°C	2 mV
S	-50°C	1760°C	2 mV
R	-50°C	1760°C	2 mV
B	400°C	1820°C	2 mV
E	-200°C	1000°C	2 mV
T	-200°C	400°C	2 mV
N	-200°C	1300°C	2 mV
RTD 2,3,4 wires			
Pt100	-200°C	850°C	50°C
Pt1000	-200°C	200°C	50°C
Ni100	-60°C	180°C	50°C
Ni1000	-60°C	150°C	50°C
Voltage			
mV	-100 mV	+700 mV	2 mV
Volt	0 mV	10 V	500 mV
Potentiometer (Nominal value)	0 Ω	200 Ω	10%
	200 Ω	500 Ω	10%
	0.5 KΩ	50 KΩ	10%
Resistance 2,3,4 wires			
Low	0 Ω	300 Ω	10 Ω
High	0 Ω	2000 Ω	200 Ω
Current mA	0 mA	20 mA	2 mA

Input calibration (1)	
RTD	the higher of ±0.1 % f.s. and ±0.2°C
Res. Low	the higher of ±0.1 % f.s. and ±0.15 Ω
Res. High	the higher of ±0.2 % f.s. and ±1 Ω
mV, TC	the higher of ±0.1 % f.s. and ±10 uV
Volt	the higher of ±0.1 % f.s. and ± 2 mV
mA	the higher of ±0.1 % f.s. and ± 6 uA

INPUT			
Input impedance			
TC, mV	>= 10 MΩ		
Volt	>= 1 MΩ		
Current	~ 50 Ω		
Linearity (1)			
TC	± 0.2 % f.s.		
RTD	± 0.1 % f.s		
Line resistance influence (1)			
TC, mV/V	<=0.8 uV/Ohm		
RTD 3 wires	0.05 %/Ω (50 Ω balanced max.)		
RTD 4 wires	0.005 %/Ω (100 Ω balanced max.)		
RTD excitation current			
Typical	0.350 mA		
CJC Comp.			
	± 0.5°C		
Thermal drift (1)			
Full scale	± 0.01 % / °C		
CJC	± 0.01 % / °C		
Response time (10÷90% of f.s.)			
	about 400 ms		

(1) referred to input Span (difference between max. and min. values)

OUTPUT			
Output type	Min	Max	Span min
Direct voltage	0 V	10 V	1 V
Direct current	0 mA	20 mA	4 mA
Output calibration			
Current	± 7 uA		
Voltage	± 10 mV		
Output Load Resistance			
Current	< 650 Ω		
Voltage	> 4.7 KΩ		

ELECTRONIC AND CONTROL PROCESS DEVICES

www.datexel.it DATEXEL

"SMART SERIES" Temperature and signal
transmitters and converters for Din rail mounting



Application areas

SMART SERIES

17